

Bombilla LED dicroica cristal 5W GU10 3000K - 12u caja exp

HOMEPLUS[®]
special line of products



Referencia	200621044	200621045	200621046
Tipo bombilla LED	Dicroica	Dicroica	Dicroica
Potencia (W)	5W	5W	5W
Casquillo	GU10	GU10	GU10
Lúmenes útiles	380Lm	380Lm	380Lm
Temperatura (K)	3.000K	4.200K	6.000K
Temperatura funcionamiento máxima	40°C	40°C	40°C
Temperatura funcionamiento mínima	-20°C	-20°C	-20°C
Ángulo apertura (°)	120°	120°	120°
CRI	80	80	80
On/Off	15.000	15.000	15.000
Horas de vida	25.000h.	25.000h.	25.000h.
SDCM	6	6	6
Duración encendido máximo	0,1	0,1	0,1
Amperios (mA)	39mA	39mA	39mA
IP	IP20	IP20	IP20
Material principal	Cristal	Cristal	Cristal
Color principal	Transparente	Transparente	Transparente
Diámetro (mm) (Ø)	50mm	50mm	50mm
Voltaje (V) (Mínimo)	220V	220V	220V
Voltaje (V) (Máximo)	240V	240V	240V
Hz	50/60Hz	50/60Hz	50/60Hz
Tipo embalaje	Blister	Blister	Blister
Eficiencia energética	G	G	G