

Bombilla LED dicroica cristal 5W MR16 6000K - 12u caja exp

HOWEPLUS[®]
special line of products



Referencia	200621041	200621042	200621043
Tipo bombilla LED	Dicroica	Dicroica	Dicroica
Potencia (W)	5W	5W	5W
Casquillo	MR16	MR16	MR16
Lúmenes útiles	460Lm	460Lm	460Lm
Temperatura (K)	3.000K	4.200K	6.000K
Temperatura funcionamiento máxima	40°C	40°C	40°C
Temperatura funcionamiento mínima	-20°C	-20°C	-20°C
Ángulo apertura (°)	120°	120°	120°
CRI	80	80	80
On/Off	15.000	15.000	15.000
Horas de vida	25.000h.	25.000h.	25.000h.
SDCM	6	6	6
Duración encendido máximo	0,1	0,1	0,1
Amperios (mA)	623mA	623mA	623mA
IP	IP20	IP20	IP20
Material principal	Cristal	Cristal	Cristal
Color principal	Transparente	Transparente	Transparente
Diámetro (mm) (Ø)	50mm	50mm	50mm
Voltaje (V) (Mínimo)	12V	12V	12V
Voltaje (V) (Máximo)	12V	12V	12V
Hz	50/60Hz	50/60Hz	50/60Hz
Tipo embalaje	Blister	Blister	Blister
Eficiencia energética	G	G	G